



PRODUCTSPECIFICATION /

COLOURFUL

TECHNICAL SPECIFICATIONS

A. Name of product	EDEL Colourful
B. Producer Production process	EDEL GRASS B.V. GENEMUIDEN tufted, cut pile
C. Pilematerial Yarn Dtex Quality	100% Polyethylene Monofilament yarn straight /curled, U.V. stabilised 12.800/16 Dtex environment friendly
D. Primary Backing Coating Waterpermeability	100% polypropylene, UV- stabilised appr. 120 gr/m2 Carboxylated (SBR) latex, appr. 988 gr/m2 with 4mm perforationholes > 300 ml/min/100 cm2 (standard NOC*NSF)
E. Pile height Total construction height Pile weight Total weight Gauge Stitch per m1 Linear Stitch per m2 UV-stability Lightfastness Colourfastness	appr. 24 mm (stretched) ±10 % appr. 26 mm ±10 % appr. 1.500 gr/m2 ±10 % appr. 2.610 gr/m2 ±10 % 3/8" gauge 200 ±10 21.000 ±10 % DIN 53387 meets 6000 hours W.O.M. test Bluescale 1-8 > 7 according to DIN 54004 Grayscale 1-5 > 4 according to other DIN standards
F. Rollwidth Rolllength Colours	ca. 2.00 m1 + 4.00 m1 ca. 25 m1 Off black, antracite, silver, white, cream, orange, pink, lilac, turquoise, lime